

SPECIFICATION

Page 3, lines 4 - 7, please amend as follows:

- FIG. 5 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention; and
- FIG. 6 is another perspective view illustrating the L.E.D. emergency lamp of FIG. 5, constructed in accordance with the present invention;
- FIG. 7 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with an L.E.D. light adjustable and angled;
- FIG. 8 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with custom electronic modules sized and shaped for being received the battery compartment;
- FIG. 9 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with a Global Positioning Satellite (GPS);
- FIG. 10 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position;
- FIG. 11 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position; and
- FIG. 12 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position.